

623.2000-005

MULTI -WAY ADAPTOR
IP44/IP54 3P+N+E 32A 380V
200x150x80mm



EN 60309-1 (1999)
EN 60309-2 (1999)
EN 60309-1/A1 (2007)
EN 60309-1/A2 (2012)
EN 60309-2/A1 (2007)
EN 60309-2/A2 (2012)
Low voltage direct. 2014/35/EU

Commercial Series	ADAPTO Series
Synthetical description	MULTI -WAY ADAPTOR
Mounting version	PORTABLE

■ TECHNICAL CHARACTERISTICS

Rated current	32A
Rated voltage	380V
Working frequency	60Hz 50Hz
Poles	3P+N+E
Inlet supply unit	Plug IEC 309 3P+N+E 32A
Emergency push button	Not applicable
RCD protection	Not applicable
In disp. ing/tipo apparecchio	Not applicable
Max power gen.	Not applicable

■ PHYSICAL CHARACTERISTICS

Material	THERMOPLASTIC
Colour	GREY
Protection degree IP	IP44/IP54
Mounting version	PORTABLE
Typology	Portable distribut. assemblies
Version	With cable and plug

■ DIMENSIONAL CHARACTERISTICS

Dimensions	200x150x80mm
No. of available outlets	3 NR

■ DOWNLOAD

[Technical drawing \[PDF\]](#)
[Technical drawing \[DWG\]](#)
[Technical drawing \[STP\]](#)

■ OPTIONS & VARIOUS NOTES

Catalogue notes	Plug OPTIMA-REVERSE with phase inverter.
-----------------	--