



# Wallcharger Duo

Specifications

## General characteristics

Reference number	55161800 / 55161100 / 55161600 / 55321800 / 55321100 / 55321600 / 55081800 / 55081100 / 55081600 / 55081602 / 55081102 / 55081801 / 55320014 / 55320013 / 55320012 / 55321604
Reference number (Eichrecht)	55451800 / 55451100 / 55451600
Reference number (FR)	55483702 / 55483703
Dimension H x W x D (mm)	800 x 220 x 200
Casing material	Steel 2,2 mm
Standard colour	Body: Ral 6018 / Cover: Ral 9016 for 55161800 / 55321800 / 55451800 / 55081800 / 55081801 / 55320014 / 55320013 / 55160012 Body: Ral 7011 / Cover: Ral 9016 for 55161100 / 55321100 / 55451100 / 55483702 / 55081100 / 55483703 / 55081102 Body: Ral 9016 / Cover: Ral 9016 for 55161600 / 55321600 / 55451600 / 55081600 / 55081602 / 55321604
Steel treatment	Anti-corrosion (KTL) and powder coating
Weight (kg)	21kg for 55451800 / 55451100 / 55451600 / 55483702 / 55081800 / 55081100 / 55081600 / 55483703 / 55081602 / 55081102 / 55081801 25kg for 55161800 / 55161100 / 55161600 / 55321800 / 55321100 / 55321600 / 55320014 / 55320013 / 55160012 / 55321604
Number of charging points	2
Socket	Type 2, Type 2 + type E/F for 55483702 / 55483703
Cable	Type 2

## Electrical characteristics

Power output per socket	0 to 22 kW for 55483702 / 55483703 / 55451800 / 55451100 / 55451600 / 55081800 / 55081801 / 55081100 / 55081101 / 55081600 / 55081601 / 55321800 / 55321801 / 55321100 / 55321101 / 55321600 / 55321601 / 55320013 / 55320014 0 to 11 kW for 55161800 / 55161801 / 55161100 / 55161101 / 55161600 / 55161601 / 55160011 / 55160012
Operating voltage (U <sub>e</sub> ) / Rates current (I <sub>n</sub> A) for the charger	Single-phase cabling, phase + N 230V~ from 0 to 63A (determined at 20°C) Three-phase cabling, 3 phases + N 400V~ from 0 to 63A (determined at 20°C)
Operating voltage (U <sub>e</sub> ) / Rates current (I <sub>n</sub> A) per charge point	Single-phase cabling, phase + N 230V~ from 0 to 32A (determined at 20°C) Three-phase cabling, 3 phases + N 400V~ from 0 to 32A (determined at 20°C)
Impulse voltage (U <sub>imp</sub> )	4kV
Insulation voltage (U <sub>i</sub> )	230V single-phase, 500V three-phase
Frequency (f <sub>n</sub> )	50Hz/60Hz
Rated voltage	1 phase + N: 230V - 3 phases + N: 400V

Voltage tolerance (V) regardless of vehicle requirements	195V - 265V
Integrated protection system on charging station	Fuse type gG 63A
Integrated protection system per charge point	Fuse type gG 32A + RCD 40A 30mA Type B
Conditional short-circuit	100kA IEC/EN 60898-1
Allowable thermal stress in Short Circuit	16 000 A <sup>2</sup> s
Connection to the mains	Phase/Neutral, rigid cable, 2.5 to 16 mm <sup>2</sup> , screw terminals HO7 V R/U Earth, rigid cable, 2.5 to 25mm <sup>2</sup> , screw terminals HO7 V R/U
Type of load	Mode 3 charging terminal equipped with a locking system for Mode 3
Vehicle connection Mode 3 connector socket (55451800 / 55451100 / 55451600 / 55483702 / 55081800 / 55081100 / 55081600 / 55483703 / 55081602 / 55081102 / 55081801)	Type 2 3P+N (single-phase compatible) with pilots compliant with IEC 62191-1 and IEC 62196-2. Use only a manufacturer-approved plug with silver-plated contacts. Use of extension and adapter prohibited.
Vehicle connection Mode 2 connector socket (55483702 / 55483703)	Type E/F domestic 2P+E (16A-250V) depending on the local regulation Use of extension and adapter prohibited.
Vehicle connection Mode 3 attache cable connector (55161800 / 55161100 / 55161600 / 55321800 / 55321100 / 55321600 / 55320014 / 55320013 / 55160012 / 55321604)	Type 2 3P+N (single-phase compatible) with pilots compliant with IEC 62191-1 and IEC 62196-2. Use of extension and adapter prohibited. 55161800 / 55161100 / 55161600: 4m curl 3x16A 55160012: 4m straight 3x16A 55321604: 4m straight 3x32A 55321800 / 55321100 / 55321600 / 55320014 / 55320013: 8m straight 3x32A
Phase rotation on channel 2 (Rightside).	In the case of monophasic cabling (Ph+N) on the power source. Channel 2 will not be able to start charging sessions, until the phase rotation between contactor and socket are manually undone.
AC meters	MID certified, Class B according to EN 50470-1, -3
Back office protocol	OCPP 1.6 Json
Positioning	GPS
Connectivity Ethernet	RJ45 connector for 55451800 / 55451100 / 55451600 / 55483703 / 55081602 / 55081102 / 55081801 / 55320014 / 55160012

## Environment

Operating temperature	-25°C / +50°C
Storage temperature	-25°C / + 80°C
Relative humidity	0 to 90% without condensation
Protection rating	IP 54 (IEC 60529), IK 10 (EN 62262) Plugged in or not
Noise level	< 40 dBA at 1m
Product	IEC 61851-1, IEC TS 61439-7 (AEVCS)

Installation	Interior or exterior, limited access zone, intended for use by ordinary persons (DBO), assembly in cabinet (wall mounted), Pollution Degree 3, TNS, TT, compatible earthing system. In the event of an IT earthing system, this can be changed locally by adding an isolation transformer.
Electrical safety	Class 1 IEC 61140

## Electromagnetic compatibility

European standards	Low Voltage Directive 2014 / 35EU / EMC Directive: 2014 / 30 / EU
Radio technology type	GSM 2G/3G/4G, GPRS, RFID
Suitable charging cards	Mifare, Ntag and iCODE SLI cards ( <a href="#">more info</a> )



**Ecotap B.V.**

Kruisbroeksestraat 23

5281 RV Boxtel

The Netherlands

+31(0) 411 210 210

[info@ecotap.nl](mailto:info@ecotap.nl)

[www.ecotap.nl](http://www.ecotap.nl)